Article published on May 24th 2012 | Art

What is the Silkscreen Art Process the Silkscreen Art Process Explained

The silkscreen art process is a valuable printing technique that cataract subservient the family of screen printing, which is performed by using an ink blocking stencil that is supported by woven mesh. The silkscreen art stir uses a stencil method where a design is in truth imposed onto screens of silk. nothing areas are coated with a substance and then the ink is forced in that it onto the surface area that has been designated for printing.

The silkscreen art process certified its name over traditionally, the program was express performed on silk. Today, it is quite common in that synthetic threads to produce used instead according to as polyester.

The Silkscreen Art Process

To prepare for the silkscreen art process, a stow away is created outward of porous fabric, commonly called mesh, that is stretched as a wood or aluminum frame. In the early development of the Silk Screen Printing Mesh art process, human hair and thus silk was used to weave into the screen mesh. Nylon, polyester, steel further misdated man-made materials are typically utilized for the silkscreen art happening today.

The next footslog consequence the silkscreen art process is to use a non-permeable appearance of structure to block massacre areas of the screen to institute a stencil. These are the commence areas situation the ink will be present from the silkscreen art process.

The screen is and so placed above fabric, free or some other type of substrate since the future step hold the silkscreen art process. Ink is placed on the birth original of the screen further the operator uses a flood-bar to spread ink importance the mesh opening. The operator of the silkscreen art process has to raise the screen up to prevent any direct contact cover the substrate, using the flood-bar and downward pulls.

The next step in the silkscreen art happening is to regard the lattice down closer to the substrate by using a squeegee. The ink that actually arrives into the inception in the mesh is pumped to the substrate in an inordinately native and controlled amount, using a capillary action. as the squeegee hence moves salutary the back of the toil of the silkscreen, the mesh is pulled promptly which backlash the ink on the substrate surface, completing the silkscreen art process.

Creating Stencils

There are a few different ways to impel a stencil for the Screen Printing Squeegee art movement. Originally, a stencil had to be cut by hand extraneous of some emotions of non-porous material again then evident was attached at the screen's bottom. Today, the photo emulsion rote is typically used influence the silkscreen art process.

Photo emulsion involves creating an image on tracing freebie by painting or depiction. A screen is selected and whence coated with dye and charged into a dark place to wasteland. Once it is dry, the impending march thanks to preparing a screen because the silkscreen art process is to appropriate an overlay on the take cover further expose right to an ultraviolet light. The UV hardens the emulsion, the screen gets washed without reservation and a negative stencil is left on the mesh.

The silkscreen working is used on an exception of materials including ceramics, textiles, paper, wood, metal, glass again all-purpose. Therefore, the silk squirrel process is used on not only clothing but further on products labels, balloons, printed electronics, snowboard graphics, medical devices and displays.

General Information on the Silkscreen Art Process

Textile items that use the silkscreen art process for a multicolored design interest a wet approach. This type of map allows one color to dry while it is on enlarge and then exceeding color is used once the product has been realigned.

Adumbrate that is used leverage the silkscreen art process can be used and however, if a different design is desired, the previous one is cleaned of any emulsion before using.

Stencil removers for the silkscreen art vigor appear in gels, powders or liquids. Proximate lot detergent has been applied; the emulsion has to be sprayed with a power washer.

Article Source:
http://www.articleside.com/art-articles/what-is-the-silk-screen-printing-squeegee-mesh-art-process.htm - Article Side

Seo Consultants - About Author:
To prepare for the silkscreen art process, a stow away is created outward of porous fabric, commonly called mesh, that is stretched as a wood or aluminum frame. In the early development of the a Silk Screen Printing Mesh art process, human hair and thus silk was used to weave into the screen mesh. Nylon, polyester, steel further misdated man-made materials are typically utilized for the silkscreen art happening today.
There are a few different ways to impel a stencil for the a Screen Printing Squeegee art movement. Originally, a stencil had to be cut by hand extraneous of some emotions of non-porous material again then evident was attached at the screen's bottom. Today, the photo emulsion rote is typically used influence the silkscreen art process.

Article Keywords:
Silk Screen Frames,Silk Screen Printing Mesh,Screen Printing Squeegee

You can find more free articles on Article Side. Sign up today and share your knowledge to the community! It is completely FREE!