



Article Side

Better ways to Remove Broken Bolt by [James Blee](#)

Article published on February 20th 2012 | [Auto](#)

A broken bolt is a malaise of auto restores, not to point out anyone else trying to fix any piece of machinery. Various ways can be adopted to remove broken bolt. The selection of method depends upon the situation and your existing tools small easy-out kit, left hand drill bits, propane torch, electric drill and vise-grip pliers are helpful in eliminating broken bolt.

Some methods to remove broken bolt:

1. try grasping the remaining bolt with a vise grip pliers or a small pipe wrench. If a portion of the bolt where the head broke off is protruding out, patiently turn out the bolt.
2. If it is a oxidised and detained bolt; scatter the threads with stabbing oil and give it a joint hard raps with a hammer to probably release the seized bolt prior to turning.
3. in order to insert screwdriver and remove broken bolt. A slot may be slice into the top of the broken bolt.
4. If the bolt is detained, apply a slight heat.
5. A file may be used to even out the sides of the bolt in order to increase the grip.
6. Drill a hole in segment of flat steel, place and weld the strip over the broken stud. An arc welder gives best performance.
7. A screw extractor or broken bolt extractor can also come into use.
8. Use a midpoint punch in the middle of the stud. Make use of a minute diameter drill, drill a hole through the center of the stud, and then employ a drill size that accommodates the screw extractor. Then calmly plug the extraction instrument into the bolt and rear out the broken bolt.

Finally, If all these methods fail, you can rethread the hole to use a new fastener. Drill through the bolt just below its minor diameter and use a tap to rethread the hole. So by using these methods we can easily remove broken bolt.

Article Source:

<http://www.articleside.com/auto-articles/better-ways-to-remove-broken-bolt.htm> - [Article Side](#)

[James Blee](#) - About Author:

For more information on a [broken bolt removal](#), check out the info available online; these will help you learn to find the a [remove broken bolt](#)!

Article Keywords:

broken bolt removal,remove broken bolt